

DM4/RB4 Intel Huron River Platform with UMA

01

PCB STACK UP

LAYER 1 : TOP
LAYER 2 : GND
LAYER 3 : IN1
LAYER 4 : IN2
LAYER 5 : VCC
LAYER 6 : IN3
LAYER 7 : GND
LAYER 8 : BOT

POWER

AC/BATT
CONNECTOR
PG 41

SYSTEM
RESET CIRCUIT PG 7
 BATT
CHARGER PG 41
 RUN POWER SW
3VSUS, 5VSUS, 3V_S5, 5V_S5
+3V, +5V PG 42

DDR3 - SODIMM0
H=5.2 PG 13

DDR3 - SODIMM1
H=9.2 PG 14

Dual Channel DDR3
1333MHz 1.5V

FAN / THERMAL
G990P11U PG 30

Sandy Bridge

(rPGA 989)

(37.5mm X 37.5mm)

PG 3,4,5,6

32.768KHz
FDI

DMI X 4

PCH

Cougar Point

(25mm X 25mm)

PG 7,8,9,10,11,12

32.768KHz

KBC
ITE8502 PG 27

SPI
PS/2

FLASH
2Mbytes PG 27

Touchpad PG 29

Keyboard PG 29

Accelerometer
(APS) PG 31

Discrete TPM PG 31

POWER

REGULATOR
+1.05V PG 39
 REGULATOR
1.5VSUS, 0.75VSMDR_VTERM,SMDR_VREF PG 36
 REGULATOR
+1.8V,+0.85V PG 39,38

CPU Core
VCC_CORE PG 35
 DC/DC
3.3PCU, 5VPCU, 15VPCU PG 40
 VGA Core
UMA PG 35

LVDS

Panel Connector
PG 15

Display Port Connector
PG 16

DP

CRT

CRT Switch
SN74CBT3257CPWR PG 17

CRT Connector(System)
PG 17

CRT Connector(Dock)
PG 33

SATA

eSATA(Dock) PG 33

USB2.0 x 1

Re-Driver PG 22

USB2.0 x 3

USB conn x 3 PG 22,23

PCIEx1

LAN
RTL8111DL PG 20

25MHz

LAN Switch
P13L500-AZFEX PG 19

AC-DC
Battery
DC-DC PG 41

RJ45/Magnetics PG 20

EXPRESS-CARD
R538 PG 26

MINI-CARD
WLAN/WiMAX PG 25

MINI-CARD
WWAN/mSATA PG 24

Dock
P 33

USB I/F
VGA I/F
Audio I/F
eSATA I/F
RJ45
Dock Ctrl
DVI
Display Port(DP0,DP1)


www.rosefix.com

Table of Contents


PAGE	DESCRIPTION
01	LOCK DIAGRAM(UMA)
02	FRONT PAGE
03-06	Sandy Bridge
07-12	Cougar Point-PCH
13-14	DDRIII SO-DIMM
15	LCD CONN
16	Display Port
17	CRT CONN
18	AUDIO CODEC(ALC269Q)
19	LAN SW
20	LAN(8111DL-VB
21	SATA HDD/CD-ROM
22	USB X1/USB+ESATA
23	USB X2/SIM_CARD/LEDs/RF
24	MINI-Card (WWAN/SSD)
25	MINI-Card (WLAN/Wimax)
26	Express Card
27	KBC IT8518/19
28	B/T
29	K/B, T/P
30	FAN & THERMAL
31	G-SENSOR/TPM
32	Daughter Boards
33	Docking CON
34	iTPM & RFID EEPROM
35	+VCC_CORE(ISL95831)
36	+1.5V_SUS/VTT (UPI6163)
37	Blank
38	+VCCSA
39	+1.05V (OZ8115)
40	SYSTEM 5V/3V
41	CHARGER (ISL88731)
42	Discharg
43	Power Block Diagram
44	XDP
45	Schematic Value Descript
46	GC9E HOLE & SCREW
47	BOM Matrix Table

Power States

POWER PLANE	VOLTAGE	PAGE	DESCRIPTION	CONTROL SIGNAL	ACTIVE IN
VIN	10V~+20V	15,35,36,38,39,40,41,42	MAIN POWER		S0~S5
+3V_RTC	+3.0V~+3.3V	7,8,11,27	RTC		S0~S5
3VPCU	+3.3V	8,13,14,15,20,27,32,33,39,40,41,42,44	IT8518/19 POWER	3V5V_EN	S0~S5
5VPCU	+5V	13,21,27,36,38,39,40,41,42	DC/DC POWER IC SOURCE	3V5V_EN	S0~S5
+15V	+15V	15,31,36,40,42	LARGE POWER	3V5V_EN	S0~S5
LANVCC	+3.3V	19,20,33,42	LAN POWER	LAN_ON	
5V_S5	+5V	11,22,23,42	PCH SUS POWER	S5_ON	S0~S3
3V_S5	+3.3V	3,7,8,9,10,11,22,23,25,27,34,42	Sys Management,PCH Resume Well, USB,WLAN,WiMAX POWER	S5_ON	S0~S3
5VSUS	+5V	15,35,42	SLP_S4# CTRLD POWER	SUSON	S0~S3
3VSUS	+3.3V	23,26,27,42	SLP_S4# CTRLD POWER	SUSON	S0~S3
+1.5VSUS	+1.5V	3,11,13,14,36,42	DDR3 SODIMM POWER	SUSON	S0~S3
0.75VSMDDR_VTERM	+0.75V	13,14,36,42	DDR3 SODIMM REFERENCE POWER	MAINON	S0
+5V	+5V	7,8,11,16,17,18,21,27,29,30,42	SLP_S3# CTRLD POWER	MAINON	S0
+3V	+3.3V	7,8,9,10,11,13,14,15,16,17,18,20,21,22,23,24,25,26,27,28,30,31,32,33,34,35,36,38,39,40,42,44	SLP_S3# CTRLD POWER	MAINON	S0
+VCC_GFX		5,35,42	VGA CORE POWER	MAINON	S0
+VCCSA	+0.8V~+0.9V	5,38,42	Sandy Bridge Power	MAINON	S0
+1.8V	+1.8V	5,8,11,39,42	LVDS,NVM POWER	MAINON	S0
+1.05V	+1.05V	3,5,7,8,9,11,39,42	Sandy Bridge VTT POWER/PCH CORE POWER	MAINON	S0
+VCC_CORE		5,35,42	CPU CORE POWER	VRON	S0
LCDVCC	+3.3V	15	LCD Power	ENVDD	S0
+5V_ODD	+5V	21	ODD Power	ODD_5V_ON	S0
+5V_HDD	+5V	21	HDD Power	MAINON#	S0
BAT-V	+10V~+17V	41	MAIN BATTERY	CHG_PBATT	S0~S5
+1.5VCPU	+1.5V	3,5,36,42	DDR3 1.5V Rails	PS_S3CNTRL	S0




Sandy Bridge Processor (DDR3)




Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	SNB 214 (DDR3 I/F)	1A


Date: Friday, December 24, 2010 Sheet 4 of 53



Sandy Bridge Processor (GND)



Sandy Bridge Processor (RESERVED, CFG)



Processor Strapping


The CFG signals have a default value of '1' if not terminated on the board.

	1	0
CFG2 (PEG Static Lane Reversal)	Normal Operation	Lane Reversed (Default)
CFG4 (DP Presence Strap)	(Default) Disable; No physical DP attached to eDP	Enable; An ext DP device is connected to eDP
CFG7 (PEG Defer Training)	(Default) PEG train immediately following xxRESETB de assertion	PEG wait for BIOS training



11(Default)

CFG[6:5] (PCIe Port Bifurcation Straps)


11: (Default) x16 - Device 1 functions 1 and 2 disabled
 10: x8, x8 - Device 1 function 1 enabled ; function 2 disabled
 01: Reserved - (Device 1 function 1 disabled ; function 2 enabled)
 00: x8,x4,x4 - Device 1 functions 1 and 2 enabled



07




U37D



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	PCH 1/6 (DMI/FDI/VIDEO)	1
Date:	Friday, December 24, 2010	Sheet 7 of 53

08



HDA Bus(CLG)

ACZ_SYNC 1 3 ACZ_SYNC_R

Q1202
2N7002

R846B 2 10K_4

+5V

C428
*10P/50V/COG_4@NC


(18) ACZ_BIT_CLK_AUDIO R8333 33 4 ACZ_BCLK

(18) ACZ_SYNC_AUDIO R8334 33 4 ACZ_SYNC


(18) ACZ_RST#_AUDIO R8335 33 4 ACZ_RST#

(18) ACZ_SDOUT_AUDIO R8336 33 4 ACZ_SDOUT


Place near the audio codec




09



Cougar Point (GPIO,VSS_NCTF,RSVD)



GPIO Pull-up/Pull-down(CLG)





BOARD ID SETTING


Board ID For Function	ID2 GPIO38	ID1 GPIO37	ID0 GPIO36
SDV	0	0	0
SIV	0	0	1
STT	0	1	0
SVT	0	1	1
SOVP	1	0	0

	BOARD_ID3 GPIO39
w/ Dock	0
w/o Dock	1

Model ID	MODEL_ID0
14"	0
15"	1



TPM physical presence	
PCH_GPIO57	Low: Default







Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	PCH 4/6 (GPIO/MISC)	1A
Date:	Friday, December 24, 2010	Sheet 10 of 53


POWER




POWER



IBEX PEAK-M (GND)



IBEX PEAK-M (GND)




Quanta Computer Inc.

PROJECT : DM4/RB4

Size	Document Number	Rev
	PCH 6/6 (GND)	1A

Date: Friday, December 24, 2010 Sheet 12 of 53




4




3




Date: Friday, December 24, 2010




Size	Document Number	Rev
	DDR3 DIMM0-RVS (5.2H)	1A
Date:	Friday, December 24, 2010	Sheet 13 of 53




LCDVCC



EC-B-04






(7,8,9,10,11,13,14,16,17,18,20,21,22,23,24,25,26,27,28,30,31,32,33,34,35,36,38,39,40,42,44)
(31,36,40,42)
(35,42)
(8,20,27,32,33,38,39,40,41,42,44)
(35,36,38,39,40,41,42)
(7,8,11,16,17,18,21,27,29,30,42)




15


back light




CAMERA VCC Control




16



The diagram illustrates a USB connector assembly with four components connected in series. The components are represented by rectangular blocks with labels inside: "Display Port Connector", "ESD TVS IC", "AC Capacitancer", and "Switch IC". Each component is connected to the next by a thick black horizontal line, indicating a series connection.





The diagram illustrates the CRT section of the EC-B-11 board, featuring two integrated circuits (ICs) labeled U10 and U17, both of type TVLST2304AD0.

U10 (TVLST2304AD0) Connections:

- Pin 1: IO1, connected to CRT R1.
- Pin 2: GND, connected to ground.
- Pin 3: IO2, connected to DDCDAT3.
- Pin 4: REF, connected to CRT B1.
- Pin 5: IO3, connected to CRT G1.
- Pin 6: IO4, connected to CRT VCC_R.


U17 (TVLST2304AD0) Connections:

- Pin 1: IO1, connected to CRT VCC_R.
- Pin 2: GND, connected to ground.
- Pin 3: IO2, connected to CRT VSYNC.
- Pin 4: REF, connected to CRT VSYNC.
- Pin 5: IO3, connected to CRT VSYNC.
- Pin 6: IO4, connected to DDCCLK3.

The diagram also shows a dashed red box labeled "EC-B-11" and a ground symbol connected to the CRT VCC_R line.


SEL	FUNCTION(COM)
LOW	IN_x0
HIGH	IN_x1




HDAudio Codec



	VA	VB
R372	3.3K	2K
R640	ASM	
R628	ASM	
U3503	ASM	
R644		ASM
R629		ASM
C673		ASM
L17		ASM
C34	ASM	
R637		(*)

*:Reserve for New combo feature






Note 1: The Trace length between L1 and 8111DL's Pin 1 must be within 0.5 cm. C5 and C8 to L1 must be within 0.5cm. Refer to Layout guide for more detail.

* C5110 to C5113 are for U5006 VDD33 pins-- 1, 29, 37 and 40.

Place C5113, C5094 closed to U5006 pins 44, 45.




* C5116 and C5273 are for U5006 EVDD12 pin 19.


* C5119 to C5123 are for U5006 VDD12 pins-- 10, 13, 30, 36, 39.

Layout: All termination signal should have 20 mil trace

Transformer



RJ45 Connector






SATA Connector.



(7,8,11,16,17,18,27,29,30,42) +5V
(7,8,9,10,11,13,14,15,16,17,18,20,22,23,24,25,26,27,28,30,31,32,33,34,35,36,38,39,40,42,44) +3V



21



ODD Connector



[illegible]

Diagram showing the connection of USB1+ and USB1- signals to the CN11 connector. The USB1PWR signal is connected to pin 1. The USB1+ signal is connected to pin 2. The USB1- signal is connected to pin 3. The ground signal is connected to pin 4. The CN11 connector is labeled 87213-0600.

USB 1

(9) USBP0+
(9) USBP0-

R39

*0.4@NC

CML1

1 2
4 3

DLW21HN9005Q2L

R38

*0.4@NC

ICH_USBP0+ C
ICH_USBP0- C

EC-B-11

U3

IO1 VIN 4
IO2 GND 1

PJSR05

USB0PWR

ESATA TX4-
ESATA TX4+

U27

IO1 VIN 4
IO2 GND 1

PJSR05

+3V

ESATA RX4-
ESATA RX4+


U26

IO1 VIN 4
IO2 GND 1


PJSR05

+3V


EC-B-11




The diagram shows two identical modules, U27 and U26, each a PJSR05 component. Each module has two input lines (ESATA TX4- and ESATA TX4+), a 3V power supply, and a ground connection. The module pins are labeled I01, I02, VIN, and GND.




EN	B0	B1	FUNCTION
0	X	X	Standby
1	0	0	Standard SATA Output
1	1	0	Ch 0 Boost Output
1	0	1	Ch 1 Boost Output
1	1	1	Ch 0.1 Boost Output






SIM Card CONN




Layout Note:
UIM_RESET, UIM_CLK, UIM_DATA routing as short as possible






	w/ WWAN	w/o WWAN
CN29	ASM	NO ASM
U46	ASM	NO ASM
C480-C481	ASM	NO ASM
C483-C485	ASM	NO ASM

FRONT LEDs




(7,8,9,10,11,13,14,15,16,17,18,20,21,22,24,25,26,27,28,30,31,32,33,34,35,36,38,39,40,42,44)
(8,15,20,27,32,33,38,39,40,41,42,44)
(26,27,42)

(11,22,42)
5V_S5
+3V
3VPCU
3VSUS



MiniCard WWAN connector

24




	w/ WWAN	w/o WWAN
CN27	ASM	NO ASM
R489	ASM	NO ASM
R484	ASM	NO ASM
R483	ASM	NO ASM
C1000~C1004	ASM	NO ASM







MiniCard WLAN/WiMAX connector

(7,8,9,10,11,13,14,15,16,17,18,20,21,22,23,24,26,27,28,30,31,32,33,34,35,36,38,39,40,42,44)
(11,24,26,36)
(8,15,20,27,32,33,38,39,40,41,42,44)
(15,35,36,38,39,40,41,42)

+3V
+1.5V
3VPCU
VIN




25




Express Card

(7,8,9,10,11,13,14,15,16,17,18,20,21,22,23,24,25,27,28,30,31,32,33,34,35,36,38,39,40,42,44) +3V
(11,24,25,36) +1.5V
(23,27,42) 3VSUS

26






BLUETOOTH

(7,8,9,10,11,13,14,15,16,17,18,20,21,22,23,24,25,26,27,30,31,32,33,34,35,36,38,39,40,42,44)

+3V

28




Quanta Computer Inc.

PROJECT : DM4/RB4

Size	Document Number B/T	Rev 1A
Date:	Friday, December 24, 2010	Sheet 28 of 53


KEYBOARD

KEYBOARD connector




29

Touch pad



TRACK POINT



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	K/B, T/P	1A

Date: Friday, December 24, 2010 Sheet 29 of 53




FAN CONTROL

(7,8,9,10,11,13,14,15,16,17,18,20,21,22,23,24,25,26,27,28,31,32,33,34,35,36,38,39,40,42,44)
(7,8,11,16,17,18,21,27,29,42)

+3V
+5V




30




G-SENSOR (2-Axial)

31



Discrete TPM




supplier P/N:ST19NP18ER28PVMK
Quanta P/N:AL19NP18K27
F/P:tssop28-6_4-65-1_2h




Quanta Computer Inc.
PROJECT : DM4/RB4

Daughter Boards for LEDs & Ports

FFC TO KBD LEFT SIDE CONNECTOR



FFC TO LED RIGHT SIDE CONNECTOR





iTPM ENABLE/DISABLE




iTPM Function	R366
Enable	1K
Disable	NC


(8) SPI_CS0#_R
(8) SPI_CLK_R
(8) SPI_SI_R
(8) SPI_SO

SPI_CS0#_R
SPI_CLK_R
SPI_SI_R
SPI_SO



R377 *SHORT 4 SPI_CS0#
R365 *SHORT 4 SPI_CLK
R362 *SHORT 4 SPI_SI
R378 *SHORT 4 SPI_SO_R
EC-C-09



For PCH
32Mbit (4M Byte), SPI





RFID



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	iTPM & RFID EEPROM	1A
Date:	Friday, December 24, 2010	Sheet 34 of 53








Quanta Computer Inc.
PROJECT :

Size	Document Number	Rev 1A
Date: Friday, December 24, 2010	Sheet 37 of 53	



A vertical bar is divided into four segments labeled A, B, C, and D from bottom to top. A horizontal arrow points to the boundary between segments B and C.


A vertical bar is divided into four segments labeled A, B, C, and D from bottom to top. A horizontal arrow points to the boundary between segments B and C.




Quanta Computer Inc.
PROJECT :

Size	Document Number	Rev
	+1.05_PCH (OZ8115)	1A


Date: Friday, December 24, 2010 Sheet 39 of 53






CPU XDP Connector

Signal Ref	Loc	Enable	Disable
TD0	R7021	ASM	NC
TRST#	R9269	ASM	ASM
DBRST#	R7076	ASM	ASM
RESET#	R7065	ASM	NC
CFG0	R7063	ASM	NC
PWRGD	R7064	ASM	NC
SYS_PWROK	R7087	ASM	NC
Conn	CN7028	ASM	NC



PCH XDP Connector

Signal Ref	Loc	Enable	Disable
TD0	R7023/R7024	ASM	NC
TMS	R7027/R7029	ASM	ASM
TDI	R7025/R7026	ASM	ASM
TCK	R9267	ASM	NC
MPWRG	R7067/R7079	ASM	NC
Conn	CN7029	ASM	NC



Quanta Computer Inc.
PROJECT : PD3

Size	Document Number DXP	Rev 1A
Date:	Friday, December 24, 2010	Sheet 44 of 53

Revision History

Revision	Date	Phase	Change List	Release Schematic Date	Release Gerber File Date
1A		DV	Initial release		

Schematic Value Explanation Description :

RESISTOR














Value	F	4	6	8	12	1210	*	Description
*1K/F_4	1%	0402 (1005)					DE POP	1K ohm 1% SMD 0402 package and DE POP
1K_6	5%		0603 (1608)				POP	1K ohm 5% SMD 0603 package and POP
1K_8	5%			0805 (2125)			POP	1K ohm 5% SMD 0805 package and POP
1K_12	5%				1206 (3216)		POP	1K ohm 5% SMD 1206 package and POP
1K_1210	5%					1210 (3225)	POP	1K ohm 5% SMD 1210 package and POP

CAPACITOR

Value	Voltage	Material	6				*	Description
*0.1U/10V/X5R_4	10V	X5R	0402 (1005)				DE POP	0.1UF 10V X5R SMD 0402 package DE POP
1U/25V/X7R_6	25V	X7R	0603 (1608)				POP	0.1UF 25V X7R SMD 0603 package POP



PROJECT: GC9A
Quanta Computer Inc.



[illegible]

2010	EC NO.	PG.	DATE	PART REFERENCE	DESCRIPTION
SDV~SIV	EC-A-01	27	07/05	U15,C135,C136,Y2	Change connection of MIC_MUTE_LED# and SPEAKER_MUTE_LED#, and reserved crystal for IT8518 per EC engineer request.
	EC-A-02	17	07/05	D20,D21,D22,D23, D24,D25,D26,D28, U10,U17	Change ESD protection component per ESD engineer request.
	EC-A-03	14	07/06	R9047,R9048, Q9000,Q9004	Add switch on SMBUS which connect to memory thermal sensor.
	EC-A-04	3,8	07/07	R390	Add connection to PROC_SELECT#
	EC-A-05	13	07/13	R8001	Alert pin have two pullup.R8001set no ASM.
	EC-A-06	18	07/21	R91,R87	NORAM loud beep fix
	EC-A-07	16	07/26	R1740	According to VESA DP interoperability guideline, R1740 value should be 5M or Larger for Dual-mode Device which support both Display port 1.1a and HDMI.
	EC-A-08	27	07/28	C127,R148	Change C127 to 0ohm, change R148 to 0ohm and not stuff for version B KBC(IT8518) per ITE fae suggestion.
	EC-A-09	27	07/28	C135,C136,Y2	Add crystal for EC
	EC-A-10	08	07/30	R9146,R8357	Remove redundant resistor R9146 and replace it by R8357 in PCH Strap Table
	EC-A-11	10	08/02	R9143,R9144, R8357	Remove R8456 and add pull high 10K resistor R9143,R9144 base on INTEL Design Guideline.
	EC-A-12	14	08/02	R8000,R8037	Change CPU FET/DDR3 thermal sensor to EMC1422-1-ACZL-TR which Local/Remote Thermal Shutdown Limit define by Hardware, for DMRB4, default Thermal Shutdown Limit value will be set on 105 degree celcius.
	EC-A-13	27	08/13	R129,Q24,CN37	Change PWR_LED# power rail to 3V_S5 and remove Q24 to prevent LED flash at the first time when insert adapter.
SIV~SIT	EC-B-01	07	09/06	R413	Power good:pull up 200ohm
	EC-B-02	21	09/06		ODD: reserve +5v path
	EC-B-03	18,27	09/06	R184,R192,D18, D19,R376,R375	Audio :change HP jack in circuit for realtek/lenovo recommend Add: R184,R192,D18,D19,R376 Delete: R375
	EC-B-04	15	09/06	CN3,CN13	Merge LCD+Camera connector same as DMRB3.
	EC-B-05	27	09/06		Correct the netname from H_PROCHOT#_EC to H_PROCHOT_EC which cause wrong define on EC setting and result of slow system issue.
	EC-B-06	27	09/06		Correct the netname assign of SUSON and S5_ON
	EC-B-07	03	09/09	U8250	Change U8250 to 74AHC1G09(OD AND gate)
	EC-B-08	24	09/09	CN27	Add AT3.0 hook connection to WWAN connector
	EC-B-09	44	09/27		Change PCH XDP signal pull up power rail from 3VPCU to 3V_S5 according to Intel CRB (Huron River Platform Emerald Lake Revision 1.0 June 2010)
	EC-B-10	07	09/28	R8292	Change connection to RSMRST# due to GC89E do not support the Deep Sx state.
	EC-B-11	16,17, 20,22, 23	09/28	C10,C1411,R45,R46, RV4,U1600, U1900, U2300,U3,U26,U27, U48,U49,C173,	Add for ESD
	EC-B-12	26	09/30	Q5	Change Q5 to 2SK3018 from DTC115
	EC-B-13	7	09/30	R8486,R8342	Add WWAN detection circuit
	EC-B-14	8,9, 20	09/30	C135,C136,C8360, C8362,C8388, C8389	Fine tune crystal shunt capacitance Y2(C135=C136=10pF),Y8200(C8360=C8362=15pF),Y8202(C8388,C8389=27pF),Y1 no need modify
	EC-B-15	22	1005	C56,C9222,R630,U53	Change from AUO3 to AUO4(TPS2254)



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	KBC IT8518/19	1A
Date:	Friday, December 24, 2010	Sheet 48 of 53

2010	EC NO.	PG.	DATE	PART REFERENCE	DESCRIPTION
	EC-B-16	24	10/06	R8549,R8550, R8551	Add 0ohm optional resistor on AT 3.0 hook signals connection.
	EC-B-17	7,8, 11	10/06	R8345,R8393,R8503, R8509,R8341	GC89E didn't support DSW function,change some power rail to non-DSW power.
SIT~SVT	EC-C-01	10	12/06		Add GPIO 39 Dock w/,w/o for Assembly request
	EC-C-02	20	12/06	R8355,R8356,RV8,RV9	ESD team recommend
	EC-C-03	20	12/06	C173	Final solution from ESD,EMI and safety team.
	EC-C-04	27	12/06		Solve issue ODD Drive LED turn on once at Battery pack plugged, change ODD_5V_ON connection from GPIO#86 to GCPIO#98.
	EC-C-05	3	12/06	C8237	Add 0.1u cap for +1.5VCPU per ESD request.
	EC-C-06				Cancel this EC
	EC-C-07	10,24 ,27	12/09	R8331,R638,R8023	Modify for mSATA and WWAN exclusive support design
	EC-C-08	20,27	12/16		Connect U15 pin120 to RJ45_LINKUP# for LAN cable detection under S5 state
	EC-C-09	3,5,7, 8,9, 10,11, 13,14, 18,24, 25,27, 33 34	12/17	R8222,R8225,R8254, R648,R8566,R8291, R8292,R8294,R8295, R8296,R8297,R8298, R8301,R8303,R8344, R8393,R9023,R8564, R7061,R8238,R9141, R8500,R8503,R8504, R8506,R8507,R8510, R8511,R8513,R8514, R8519,R8522,R8523, R8524,R8525,R8526, R8528,R8529,R8530, R8531,R8532,R8533, R8534,R8538,R8542, R8546,R8002,R8022, L17,R629,R635,R636, R644,R8549,R8550,R8551, R309,R318,R319,R320, R321,R322,R323,R324, R325,R478,R9262,R362, R365,R377,R378	Change 0 ohm to shortpad.
	EC-C-10	5,11	12/21	C8541,C8542,C8543,RV10, RV11,RV12,RV13,RV14	Reserve 0.1u and 0402 TVS space for ESD



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	KBC IT8518/19	1A
Date:	Friday, December 24, 2010	Sheet 49 of 53

2010	EC NO.	PG.	DATE	PART REFERENCE	DESCRIPTION
	EC-C-11	27	12/24	R123,R124	Change power rail from 3VPCU to 3V_S5
	EC-C-12	18	12/24	C45	Change from 2.2u to 1u to solve pop noise when resume from S3
	EC-C-13	11,16	12/24	RV15,C8460,C8465,C8466, C8467,C8468,C8469, C8470,C1412	Add for ESD display port CDE solution.
SIT~SVT					

EC NO	PG.	DATE	PART REFERENCE	DESCRIPTION
EC-P-01	35	7/6	PR7007	change from 2.37K to 2.32K
EC-P-02	35	7/6	PR9059	change from 27.4K to NC(*)
EC-P-03	35	7/6	PC9058	change from 0.068u to 0.022u
EC-P-04	35	7/6	PC9059	change from 0.068u to 0.015u
EC-P-05	41	7/6	PR107	change from 10K to 4.7K
EC-P-06	36	8/17	PQ82	change to NC(*) for S3 issue
EC-P-07	38	8/17		change 5VPCU to 3VPCU for 0Z8117 new version
EC-P-08	40	9/7	PC192	change to NC(*)
EC-P-09	39	9/7	PR278,PR282	change PR278 to 12.7K,change PR282 to 10K for +1.8V ripple
EC-P-10	39	9/7	PR9170	change PR9170 to 51.1K for +1.05V regulation
EC-P-11	39	9/7	PL12	change PL12 to 1uH for +1.05V ripple
EC-P-12	39	9/7	PR9166	change PR9166 to 97.6K for +1.05V OCP
EC-P-13	39	9/7	PC9142	change PC9142 to 4700pF for +1.05V transient
EC-P-14	38	9/7	PR9130	change PR9130 to 2.2ohm for +VCCSA Ringing voltage
EC-P-15	38	9/7	ER9133,EC9114	Add ER9133 to 4.7ohm and add EC9114 to 1000pF for +VCCSA Ringing voltage
EC-P-16	36	9/7	PR124	Change PR124 to 10K for 1.5V regulation
EC-P-17	38	9/7	PR9137	Change PR9137 to 78.7K for +VCCSA OCP
EC-P-18	36	9/7	PR122	Change PR122 to 4.53K for 1.5V OCP
EC-P-19	40	9/7	PR255	Change PR255 to 267K for 3VPCU OCP
EC-P-20	40	9/7	PR262	Change PR262 to 249K for 5VPCU OCP
EC-P-21	36	9/8	PR9245	S3 Function Modify
EC-P-22	35	9/8		Change for CPU transient quality
EC-P-23	35	9/8		Change for GFX transient quality



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	EC	1A
Date:	Friday, December 24, 2010	Sheet 51 of 53

EC NO.	PG.	DATE	PART REFERENCE	DESCRIPTION
EC-SIT-01	35	9/28	PR9049,PR9050 PR28,PR29 PR30,PR19 PR20,PR152 PR153,PR15 PR13,PR22 PR26,PR9055	change to short-pad
	36	9/28	PR195,PR207 PR196,PR199 PR200,PR125	change to short-pad
	38	9/28	PR9129,PR9136 PR9145,PR9239	change to short-pad
	39	9/28	PR9160,PR9168 PR274,PR9163 PR9157	change to short-pad
	40	9/28	PR270,PR250 PR263,PR261 PR256,PR285 PR249,PR260	change to short-pad
	41	9/28	PR1008,PR113 PR111,PR108	change to short-pad
EC-SIT-02	42	9/28	PR9228,PC9190 PQ9050,PR9227 PQ9051,PD32	change to NC for HW request
EC-SIT-03	38	9/28	PR9139,PR9140	Reduce leakage current
EC-SIT-04	35	10/1	PR9053,PR2,PR3	Intel VBoot setting to 0V request



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	EC	1A
Date:	Friday, December 24, 2010	Sheet 52 of 53

EC NO.	PG.	DATE	PART REFERENCE	DESCRIPTION
EC-SVT-01	35	11/24	PR9053 PR9054	change PR9053 to 1.69K for CPU Iccmax change PR9054 to 24.9K for CPU Iccmax
EC-SVT-02	35	11/30	PR9069	change PR9069 to 27.4K for when Iccmax=53A Vimon can within 2.7V
EC-SVT-03	39	11/30	PU11 PR281	change PU11 to UP0104PSU8 change PR281 to 0hm for HW requrest
EC-SVT-04	35	12/10	PC103 PC9201 PR9246	change PC103 to 330uF, change PC9201 to 330pF, change PR9246 to 20k for GFX OVP issue
EC-SVT-05	35 36 38 39 40 41	12/21	PL8,PL9,PL10, PL15,PL12,PL1006 PL19,PL20 PL14	DC to CV inductor p/n change



Quanta Computer Inc.
PROJECT : DM4/RB4

Size	Document Number	Rev
	EC	1A
Date:	Friday, December 24, 2010	Sheet 53 of 53